




PERFORMANCE AND PRECISION

in every receipt

RP 3200 Lite

Thermal Receipt Printer



Sleek design,
Easy to use and
Lightweight



High print
speed of 200 mm/s



Interface:
USB | Ethernet |
RJ11 Cash drawer port



Supports
all drivers and
Utilities



Uses
ESC/POS
Standard
Protocol



Support:
CODE128,
QR CODE, etc.

RP 3200 Lite

Thermal Receipt Printer

Level	: Standard
Resolution	: 8dots/mm(203DPI)
Printing Method	: Direct Thermal
Print head	: ROHM/KAITONG
Print speed	: 200mm/second max.
Print width	: 72mm
CPU	: 144MHZ, 32 Bit Cortex-M4
Memory RAM	: 64K bytes
Memory ROM	: 256K bytes
Memory FLASH	: 32M bytes
Indicator light	: 1.FEED light 2. Error light (two lights)
Interface	: 1.USB+RJ11 CashDrawer 2.ETH+RJ11 CashDrawer 3.USB+ETH+RJ11 CashDrawer
Buzzer	: Standard
Sensors	: Reflective sensor
Paper cutting	: Auto Cutter/Tear bar
Print head life	: 150KM
Cutter life	: 1.5 million times
Printer language	: Simplified Chinese, Traditional Chinese, Japanese, Korean, ANK Character Set
Media type	: Thermal paper
Media width	: 58/80mm
Physical dimension	: 130mm (D) x 161mm (W) x 126mm(H)
Net Weight	: 1kg

For trade enquiries contact