

SMARTER FEATURES, FASTER RECEIPT BUSINESS




BUILT WITH NEXT-LEVEL FEATURES

- Voice-reminder for printed receipts
- Ultra-speed printing 350 mm/sec
- Connectivity:
USB+Serial+Ethernet

RP 3350


3-inch Voice-reminder Enabled
Thermal Receipt Printer



Chic and stylish
Industrial design



Top/front paper
loading /exit



Cutter jam
auto-elimination



Supports
ESC/POS
Commands



Suitable for all
window driver and
utility tools window

RP 3350

3-inch Voice-reminder Enabled Thermal Receipt Printer

Printing Method	: Direct Thermal
Resolution	: 203DPI
Print speed	: 350mm/second max.
Print width	: 72mm
Programming Language	: ESC/POS, XML
1D Barcode	: UPC-A,UPC-E,Code 39,Code 93,Code128, EAN8, EAN13, Interleaved 2 of 5,Codabar
2D Barcode	: QR Code, PDF417
Font	: ASCII:Font A 12x24,Font B 9x17, 46 International Character Sets
Graphics	: Support bitmap printing with different density and user defined bitmap printing. (Max size of each bitmap is 64 KB, the total size of bitmap is 256 KB)
Paper Type	: Thermal continuous receipt paper, thermal environmental receipt paper
Paper Width	: 80 mm
Roll Paper Diameter	: Max. Φ 83 mm (O.D.)
Paper Load	: Front or Top paper loading
Standard	: USB+Serial+Ethernet
Buzzer	: Built-in buzzer, External acousto-optic alarm (optional), voice reminding
Sensor	: Paper out detector, Head up detector, Cutter jam detector, overheat detector
RAM	: 4 MB
FLASH	: 4 MB
Input	: AC 100 V ~ 240 V, 50/60 Hz
Output	: DC 24 V, 2 A
Driver	: Windows 7/8/10, Windows Server 2008/2012/2016, Linux, Javapos, OPOS, MacOS
Utility	: Windows 7/8/10,Windows Server 2008/2012/2016
TPH	: 150 km
Cutter	: 1.5 million cuts
Operating	: 0°C ~ 45°C, 5% ~ 95% R.H, no-condensation
Storage	: -20°C ~ 70°C, 15% ~ 95% R.H, no-con densation

For trade enquiries contact